



GENERAL NOTES

- |  |  |                               |
|--|--|-------------------------------|
| 1. SHELL: <u>.289" SA-455</u>                  | 7. <u>M.A.W.P. 250 PSIG. @ 200 °F</u>  | 13. C.F.M. REQ'D. <u>4033</u> |
| 2. HEADS: <u>.245" SA-455 2:1 S.E. JOGGLE</u>  | <u>M.D.M.T. -20 °F @ 250 PSIG.</u>     |                               |
| 3. X-RAY: <u>RT-4 SPOT L.S. &amp; G.S.</u>     | 8. HYDRO: <u>327 PSIG. MIN.</u>        |                               |
| 4. STRESS REL., <u>NO</u>                      | 9. GAL: <u>1150</u>                    |                               |
| 5. CORR. ALLOW: <u>NONE</u>                    | 10. EMPTY WT: <u>2470# APROX.</u>      |                               |
| 6. ASME SEC. <u>VIII</u> DIV. 1, 2004 ADD 2006 | 11. <u>DEHYDRATE INSIDE</u>            |                               |
|  | 12. SURFACE AREA: <u>194.1 SQ. FT.</u> |                               |

<b>P-1150</b>	REV. 1-3-07
	DATE: 3-5-99
FOR: HANSON STANDARD	
MODEL No. 1150	
HORIZ. PROPANE TANK	
BY: J.G.	SCALE: 1/2"=12"
<b>ROY E. HANSON JR. MFG.</b>	
1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	